

tesa® 64620 Double-sided film tape

tesa® 64620 is a double-sided self-adhesive tape, consisting of a white PP-carrier and a synthetic rubber adhesive mass system (hotmelt). With the hotmelt adhesive, tesa® 64620 is solvent free and offers a high tack.
tesa® 64620 is protected by a siliconized paper liner.

Main Application

- Floor Laying
- General purpose fixing tape

Technical Data

▪ Backing material	PP film	▪ Type of liner	glassine
▪ Color	white	▪ Colour of liner	brown
▪ Total thickness	185 µm	▪ Thickness of liner	70 µm
▪ Type of adhesive	synthetic rubber	▪ Weight of liner	78 g/m ²

Adhesion to

▪ Steel (initial)	12.0 N/cm	▪ Steel (after 14 days)	26.0 N/cm
▪ PE (initial)	6.5 N/cm	▪ PE (after 14 days)	9.5 N/cm
▪ PP (initial)	10.0 N/cm	▪ PP (after 14 days)	13.5 N/cm
▪ PVC (initial)	12.0 N/cm	▪ PVC (after 14 days)	25.0 N/cm

Properties

▪ Temperature resistance short term	80 °C	▪ Static shear resistance at 23°C	●●●●
▪ Temperature resistance long term	40 °C	▪ Static shear resistance at 40°C	●●●
▪ Tack	●●●●	▪ Static shear resistance at 70°C	●●
▪ Ageing resistance (UV)	●	▪ Fogging	●●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Additional Information

Suitable for plasticizer free flooring materials

For latest information on this product please visit <http://l.tesa.com/?ip=64620>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.