productinformation

tesa[®] 4173 PV2 Soft PVC tape for basic bundling

tesa® 4173 PV2 is a PVC film wire harness tape with an acrylic adhesive.

Major Features:

- Temperature resistance 105°C/3000h
- Flexible
- Handtearable

Color: Black

Main Application

tesa® 4173 is designed for the passenger compartment for basic bundling up to a temperature class of 105°C.

Technical Data

	Backing material	PVC film
-	Dacking material	FVCIIIII
•	Total thickness	126 µm
•	Type of adhesive	acrylic
•	Adhesion to steel	1.8 N/cm
•	Elongation at break	250 %
•	Tensile strength	30 N/cm
•	Temperature resistance min.	-25 °C

	Temperature resistance (3000h)	105 °C
•	Abrasion resistance (10mm	Class A (acc. to
	mandrel)	LV312)
•	Abrasion resistance (5mm	Class A (acc. to
	mandrel)	LV312)
•	Flame resistance as composite	Class B (acc. to
		LV312)
•	Noise damping (decibel)	Class A (acc. to
		LV312)
•	Dielectric breakdown voltage	7000 volt

Additional Information

Standard widths: 9, 19, 25, 32 mm

Standard lengths: 33 m

*Most combinations of width and length are possible

*Further dimensions are available upon request

*Standard core diameter: 38 mm

For latest information on this product please visit http://l.tesa.com/?ip=04173

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

